

XBO 75 W/2

XBO | Xenon short-arc lamps without reflector



Product benefits

- Very high luminance (point light source)
- Continual color quality, irrespective of lamp type and lamp wattage
- Constant light color throughout the life of the lamp
- Long lamp life

Product features

- Color temperature: approx. 6,000 K (Daylight)
- High color rendering index: $R_a >$
- Continuous spectrum in the visible range
- High arc stability
- Hot restart capability
- Dimmable
- Instant light on starting



Technical data

Electrical data

Nominal wattage	75 W
Construction wattage	0.075 kW
Lamp wattage	64...86 W
Lamp voltage	12...16 V ¹⁾



¹⁾ Initial voltage range

Light technical data

Nominal luminous flux	1000 lm
Luminous intensity	100 cd ¹⁾
Luminous flux	1000 lm ¹⁾
Luminance	40000 cd/cm ² ¹⁾

¹⁾ Typical initial photometric value

Dimensions & weight



Product line drawing

Base


Diameter	10.0 mm
Mounting length	82.0 mm

Lifespan

Lifespan	400 h
----------	-------

Additional product data

Product datasheet



Luminous intensity distribution

Base (standard designation)	SFa7.5/SFa9
Picto Medicine	Yes


Country specific information

Product code	METEL code	SEG-No.	STK number	UK Org
4050300508801	OSRXB0752	-	4836307	-


Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure in both the hot and cold state, XBO lamps must only be operated in appropriate enclosed casings. Always use the protective jackets supplied when handling these lamps. They may only be used as open lamps if appropriate safety measures are taken. More information is available on request or can be found in the leaflet included with the lamp or the operating instructions.



Burning position



Burning position

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Volume	Gross weight
4050300508818	XBO 75 W/2	Shipping carton box 10	225 mm x 210 mm x 235 mm	11.10 dm ³	1138.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

Further technical information on XBO lamps and information for manufacturers of operating equipment can be requested directly from OSRAM.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.